

Multiple Site Automated Logout

Field of the Invention

This invention relates generally to the field of computers, and in
5 particular to automatically logging out of multiple sites on computers.

Copyright Notice/Permission

A portion of the disclosure of this patent document contains material,
which is subject to copyright protection. The copyright owner has no objection
10 to the facsimile reproduction by anyone of the patent document or the patent
disclosure as it appears in the Patent and Trademark Office patent file or records,
but otherwise reserves all copyright rights whatsoever. The following notice
applies to the software and data as described below and in the drawing hereto:
Copyright © 2000, Microsoft Corporation, All Rights Reserved.

15

Background

The recent growth in popularity of the Internet has significantly increased
the number of Internet users and the number of Internet sites (also referred to as
“web sites”). Web sites may provide various types of information to users, offer
20 products or services for sale, and provide games and other forms of
entertainment. Many web sites require users to “register” by providing
information about themselves before the web server grants access to the site.
This registration information may include the user’s name, account number,
address, telephone number, email address, computer platform, age, gender, or
25 hobbies. The registration information collected by the web site may be
necessary to complete transactions (such as commercial or financial
transactions). Additionally, information can be collected which allows the web
site operator to learn about the visitors to the site to better target its future
marketing activities or adjust the information provided on the web site. The
30 collected information may also be used to allow the web site to contact the user

directly (e.g., via email) in the future to announce, for example, special promotions, new products, or new features of the web site.

When registering with a web site for the first time, the web site typically requests that the user select a login ID and an associated password. The login ID
5 allows the web site to identify the user and retrieve the user's information during subsequent user visits to the web site. Generally, the login ID must be unique to the web site such that no two users have the same login ID. The password associated with the login ID allows the web site to authenticate the user during subsequent visits to the web site. The password also prevents others (who do not
10 know the password) from accessing the web site using the user's login ID. This password protection is particularly important if the web site stores private or confidential information about the user, such as financial information or medical records.

If a user visits several different web sites, each web site may require
15 entry of similar registration information about the user, such as the user's name, mailing address, and email address. This repeated entry of identical data is tedious when visiting multiple web sites in a short period of time. Many web sites require the user to register before accessing any information provided on the web site. Thus, the user must enter the requested registration information
20 before they can determine whether the site contains any information of interest.

After registering with multiple web sites, the user must remember the specific login ID and password used with each web site or other Internet service.

Without the correct login ID and password, the user must re-enter the registration information. A particular user is likely to have different login IDs
25 and associated passwords on different web sites. For example, a user named Bob Smith may select "smith" as his login ID for a particular site. If the site already has a user with a login ID of "smith" or requires a login ID of at least six characters, then the user must select a different login ID. After registering at numerous web sites, Bob Smith may have a collection of different login IDs,
30 such as: smith, smith1, bsmith, smithb, bobsmith, bob_smith, and smithbob. Further, different passwords may be associated with different login IDs due to

login server. The login server retires all login domain cookies first, and displays a page that explains to the user that they are about to be logged out of each domain. The logout page generates image tags for each of the sites listed in the visited-sites cookie. The image tag provides a URL hosted at each site that
 5 expires cookies that are present in the user's cookie cache by setting their value to nothing, and their expiration date to a past date.

When a request to logout is received, the Visited Sites cookie is checked, and if present, it is read. All local cookies are then expired, and indicated as such on a user interface. In order to avoid redirecting the user to each domain,
 10 the logout page provides an individual image source for each site the user signed into. This enables the login server to log the user out of each domain by clearing selected cookies stored by the domains. It also clears the cookies from the user's browser and then indicates on the logout page if the logout was successful for each domain. Finally, the domain from which the user selected to logout
 15 specifies the URL to which the user is redirected.

Brief Description of the Drawings

- Fig. 1 is a block diagram showing pertinent components of a computer in accordance with the invention.
- 20 Fig. 2 illustrates an exemplary network environment in which the present invention is utilized.
- Fig. 3 is a block diagram showing a browser, logout server, and two affiliate sites to which a user is logged into.
- Fig. 4 is a flowchart indicating the logical flow of the logout server.

25

Detailed Description

In the following detailed description of exemplary embodiments of the invention, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific exemplary
 30 embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the

invention, and it is to be understood that other embodiments may be utilized and that logical, mechanical, electrical and other changes may be made without departing from the spirit or scope of the present invention. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined only by the appended claims.

The detailed description is divided into multiple sections. A first section describes a simple representation of a computer system and the operation of multiple computer systems on a network which implement different aspect of the current invention. This is followed by a description of the invention and how it is implemented.

Hardware and Operating Environment

An exemplary system for implementing the invention includes a computing device, such as computing device 100 in Figure 1. In its most basic configuration, computing device 100 typically includes at least one processing unit 102 and memory 104. Depending on the exact configuration and type of computing device, memory 104 may be volatile (such as RAM), non-volatile (such as ROM, flash memory, etc.) or some combination of the two. This most basic configuration is illustrated in Figure 1 by broken line 106.

Device 100 may also include additional features/functionality. For example, device 100 may include additional storage (removable and/or non-removable) including, but not limited to, magnetic or optical disks or tape. Such additional storage is illustrated in Figure 1 by removable storage 108 and non-removable storage 110. Computer storage media includes volatile and nonvolatile, removable and non-removable media implemented in any method of technology for storage of information such as computer readable instructions, data structures, program modules or other data. Memory 104, removable storage 108 and non-removable storage 110 are all examples of computer storage media. Computer storage media includes, but is not limited to RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic based storage or any other medium

which can be used to store desired information and which can be accessed by device 100. Any such computer storage media may be part of device 100.

Device 100 may also contain communications connection(s) 112 that allow the device to communicate with other devices. Communications connection(s) 112 is an example of communication media. Communications media typically embodies computer readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information delivery media. The term "modulated data signal" means a signal that has one or more of its characteristics set of changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. The term computer readable media as used herein includes both storage media and communications media.

Device 100 may also have input device(s) 114 such as keyboard, mouse, pen, voice input device, touch input device, etc. Output device(s) 116 such as display, speakers, printers, etc may also be included. All these devices are well known in the art.

This invention may be described in the context of computer-executable instructions, such as program modules, executed by one or more computer or other devices such as device 110. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Typically the functionality of the program modules may be combined or distributed as desired in various embodiments.

Fig. 2 is a block diagram illustrating an exemplary network environment in which the present invention is utilized. A client computer system 200 is coupled to a network 202. In this example, network 202 is the Internet (or the World-Wide Web). However, the teachings of the present invention can be applied to any data communication network that implements a stateless protocol

similar to hypertext transfer protocol, http. Multiple affiliate servers 204, 206, and 208 are coupled to network 202, thereby allowing client computer system 200 to access web servers 204, 206, and 208 via the network. Affiliate servers 204, 206, and 208 are also referred to as "web servers", "network servers" and "sites" hosting content such as text and images for access by other computers on the network 202. An authentication server 210 is also coupled to network 202, facilitating communication between the authentication server and client computer system 200 and authentication servers 204, 206, and 208. Although referred to as an "authentication server", authentication server 210 is also a web server capable of interacting with web browsers and other web servers. In this example, data is communicated between the authentication server 210, client computer system 200, and web servers using http, a protocol commonly used on the Internet to exchange information. An http specification is published by the Internet Engineering Task Force.

15 An authentication database 212 is coupled to authentication server 210. The authentication database 212 contains information necessary to authenticate users and also identifies which elements of user profile information should be provided to a particular affiliate server when the user accesses the affiliate server. Although the authentication database 212 is shown separately from the authentication server 210, in other embodiments of the invention, the authentication database is contained within the authentication server.

20 An authentication process authenticates a user of client computer 200 seeking access to an affiliate server 204, 206, or 208. The authentication server 210 authenticates the user of client computer 200 by requesting authenticating information, such as the user's login ID and password. If the user is successfully authenticated, then authentication server 210 generates an encrypted authentication ticket and communicates the ticket to the appropriate affiliate server. The authentication ticket indicates that the user is authenticated. Each affiliate server requires a key in order to decrypt the ticket and allow access by the user.

The authentication ticket contains two time stamps. The first time stamp indicates the last time that the user's login ID and password were physically typed by the user. The second time stamp indicates the last time that the user's login information was refreshed by the authentication server. This "refresh" of the user's login information can be performed "silently" or by manual entry of the login information (i.e., login ID and password) by the user. The refreshing of the user's login information is performed by the authentication server. Once completed, a new authentication ticket is issued to the affiliate server indicating the new time stamp values.

The term “affiliate server” is defined herein as a web server that has “registered” or established a relationship or affiliation with the authentication server 210. Each affiliate server 204, 206, and 208 includes a code sequence that allows the affiliate server to communicate with the authentication server 210 when a user (who is also registered with the authentication server) requests access to the affiliate server.

Prior to executing the authentication process, both the user of client computer system 200 and the operator of affiliate server 204 “register” with the authentication server 210. This registration is a one-time process which provides necessary information to the authentication server. The user of client computer system 200 registers by providing information such as the user’s email address, password information, and various other information about the user or the client computer system if desired. As part of the user registration process, the user is assigned (or selects) a login ID, which is a common login ID used to access any affiliate server. The login ID may also be referred to herein as a “user name” or “login name”. Additionally, the user selects a password associated with the login ID which is used for authentication purposes.

After registering and logging into the authentication server, the user can visit any affiliate server (i.e., affiliate servers that are also registered with the same authentication server) without requiring any additional authentication and without re-entering user information that is already contained in the associated user profile.

authentication server also updates (or creates) a cookie that contains a list of all sites (or web servers) visited by the user since the last logout from the authentication server. This cookie is referred to as a visited sites cookie. The visited sites cookie is updated by adding the current affiliate server to the list of sites visited. The list may consist of a set of site IDs which were assigned at registration.

Due to security features implemented in current web browsers, and in compliance with the http specification, cookies written to the client computer system by the authentication server cannot be read by any affiliate server. Similarly, cookies written to the client computer system by a particular affiliate server cannot be read by any other affiliate server. The cookies written by an affiliate server are encrypted using a key that is unique to the affiliate server, thereby preventing other affiliate servers from reading the data stored in the cookies.

The authentication server also communicates the user profile information to the affiliate server through the client computer system. In a particular embodiment of the invention, the user of the client computer system can specify during the registration process what types of profile information should be provided to various types of web servers. For example, a user may specify that all commerce-related web servers should receive the user's email mail address, but restrict the mailing address from all other types of web sites.

After receiving the authentication ticket and the user's profile information, the affiliate server may generate a personalized web page for the user and communicates the web page to the user's browser. Additionally, the affiliate server copies one or more cookies to the client computer system which include information indicating that the user of the client computer system has been authenticated and indicating the period of time during which the authentication is valid. Each time the user enters a new web page request on the same affiliate server, the data in the cookie is sent to the affiliate server along with the page request. Thus, the affiliate server will not repeatedly check the authentication of a user during each subsequent page request. However, if a

particular period of time has passed (referred to as a timeout period) since the last authentication process by the authentication server, then the affiliate server may request a re-authorization of the user.

5 It is difficult for a user to individually remove each cookie when logging out of an affiliate server, or when logging out of all affiliate servers in the visited sites cookie. Since one server cannot access the cookies provided by another server, each affiliate server individually logs out each user.

10 In Figure 3, an improved way of logging a user out of each affiliate server indicated in the visited sites cookie is shown in block diagram. A browser is shown at 310 in communication with a login server 320. The browser 310 is also shown as communicating with two affiliated servers 330 and 340. The affiliated servers for purposes of this description each reside on a different domain. It should be recognized that a domain may have more than one server, and that logging into one server may log a user into multiple servers on the same domain.

15 When a user desires to log out, the user can go to any site that contains a logout link pointing to a logout page on the login server 320. This results in the browser issuing a get visited sites cookie to the login server 320. The logout service on the authentication server builds an image source tag corresponding to each site identified in the visited sites cookie by providing markup language based source to the browser as indicted at 350. Each image source tag has a site ID. Three site IDs are shown at 350, "10, 15 and 7000". The visited sites cookie may simply be the list of site IDs in text string such as: "10, 15, 7000".

20 The image source tags are rendered into a page on the browser 310 that identifies the sites in the visited sites cookie, and also provides a position for a check mark or "x" mark to indicate whether or not logout was successful for each visited site. Text is provided at the top of the page in this example: "Please wait while we sign you out". A more elaborate page may easily be created if desired. Further, text may be provided instructing the user to wait for all check marks to render, and try again later or go to individual sites directly to ensure proper logout.

Each image source tag has a query string parameter on the end of it to cause the browser go and fetch the image via a separate transaction as opposed to referring to a cache of the image. The image source tag points to an expire cookies uniform resource locator (URL) that is hosted by each affiliated server.

5 It responds with a set cookie header that clears desired cookies from the browser.

One manner of clearing such cookies is to set their value to nothing, and set their expire time to a past date. The particular cookies cleared include profiles and authorizations, as well as site cookies that were generated by the visited affiliated servers. The cookies are labeled MSPAuth (authorization), MSPPProf (profile), and site cookies in Figure 3. Affiliated servers also respond with a
10 small checkmark image which is added to the logout page on the browser to indicate successful logout. In one embodiment, code is used to look for a response from each affiliated server, and if not received in a desired period of time, it places an "x" or other symbol indicative of logout failure. Finally, the
15 affiliated server from which logout was selected may be allowed to specify the page to be displayed to the user.

One aspect of the invention involves tricking the browser to think it is fetching image source from the domains. The browser is simply issuing separate requests for images to each visited affiliated server. The affiliated servers
20 believe that they are returning just an image, but also send the set cookie header along with the checkmark which causes the browser to delete the desired cookies.

Figure 4 is a flowchart of the logical flow of the logout process. At 410, the user selects logout on any affiliate server, or the authentication server. A
25 non-secure connection is started at 415, and an incoming request to logout is received by the login server at 420. The request indicates the site ID which was assigned during registration, and may contain many of the same arguments used to log in, such as time windows and current time as well as other information if desired. It also may identify a return URL to indicate a page to direct the
30 browser to when done logging out. At 425, a check is made to determine if the visited sites cookie is present. If not, an error case occurs and is handled at 430.

If a site ID is provided, a logout user interface is rendered with a site ID expire cookie URL image tag that was specified by the site during registration. If no site ID is provided, a logout user interface indicating that "You are Signed Out" is provided. The user browser is then redirected to the domain on which logout
5 was selected.

If at 425, a visited sites cookie is found, it is read at 435. At 440, a check is made to determine if the site ID has specified a logout URL during registration. If not, all local cookies are expired and a logout user interface is rendered with all siteIDs expire cookie URL image tags with a timeout upon
10 which the browser is redirected to the domain's return URL.

If at 440, a siteID has a logout URL, all local cookies are expired and a logout user interface is rendered with all siteIDs expire cookie URL image tags with a timeout upon which the browser is redirected to the siteID logout URL.

The invention provides a simple mechanism to facilitate a user signing
15 out of multiple sites without requiring special client downloads, server to server communication or special user interaction. The invention makes it easier to securely visit password protected sites while traveling and using kiosks, or generally using any browser that multiple people may access. It may be used simply for convenience, but also may be used to minimize the risk of
20 compromising the users passwords or inadvertently providing personal or sensitive information to others.

We claim:

1. A method of logging a computer system user out of a server comprising
25 the steps of:

selecting a logout link;

generating a logout page for display on a browser being used by the user;

causing a request for data from the server to be issued by the browser,

wherein the request causes the server to expire cookies from the browser.

30

2. The method of claim 1 wherein the request further causes the server to send an image to the browser which is indicative of successful logout.
3. The method of claim 1 wherein multiple servers are logged out of by selection of a single logout link.
4. The method of claim 3 wherein the logout link may be located on any of the multiple servers and an authentication server.
5. The method of claim 3 wherein a visited sites cookie maintains a list of all sites logged into by the user.
6. The method of claim 1 wherein selected cookies are expired to log out of the server.
7. A computer readable medium having a program stored thereon for causing a computer to implement a method of logging a computer system user out of a server comprising the steps of:
 - selecting a logout link;
 - generating a logout page for display on a browser being used by the user;
 - causing a request for data from the server to be issued by the browser,wherein the request causes the server to expire cookies from the browser.
8. The computer readable medium of claim 7 wherein the request further causes the server to send an image to the browser which is indicative of successful logout.
9. The computer readable medium of claim 7 wherein multiple servers are logged out of by selection of a single logout link.

10. A method of logging a computer system user out of multiple servers comprising:

receiving a request for a logout page;

providing a link to an expire cookies page on each server that when
5 called causes each server to expire cookies on the user's browser, and to provide
an image back to the browser upon succeeding in logging the user out.

11. A system for logging a computer system user out of multiple servers comprising:

10 means for receiving a request for a logout page; and

a module that provides a link to an expire cookies page on each server
that when called causes each server to expire cookies on the user's browser, and
to provide an image back to the browser upon succeeding in logging the user out.

15 12. The method of claim 11 and further comprising maintaining a list of
servers that a user has logged into identified by site ID.

13. The method of claim 11 wherein the list of servers is used to identify the
link to each expire cookies page on each server.

20

14. The method of claim 11 wherein the request for a logout page can be
initiated via different server pages.

15. A computer readable medium having a program stored thereon for
25 causing a computer to implement a method of logging a computer system user
out of multiple servers comprising:

receiving a request for a logout page;

providing a link to an expire cookies page on each server that when
called causes each server to expire cookies on the user's browser, and to provide
30 an image back to the browser upon succeeding in logging the user out.

16. A method of logging a computer system user out of multiple servers comprising:

selecting a logout link from an affiliated server;

building a page containing an expire cookies URL;

5 sending requests to retrieve an image identified by each expire cookies URL;

retiring stored cookies; and

receiving and displaying an image from multiple servers.

10 17. A computer readable medium having a program stored thereon for causing a computer to implement a method of logging a computer system user out of multiple servers comprising:

selecting a logout link;

building a page containing an expire cookies URL;

15 sending requests to retrieve an image identified by each expire cookies URL;

retiring stored cookies; and

receiving and displaying an image from multiple servers.

20 18. A method of logging out of multiple domain servers on a network, the method performed by a browser comprising:

requesting a logout page from an authentication server;

receiving source image tags from the authentication server;

issuing get image requests to URLs identified by the image tags;

25 retiring cookies identified by responses to the get image requests; and

rendering an image received in responses from the domain servers.

19. The method of claim 18 wherein the image comprises a small image that can be loaded quickly.

30

009790"2226560

20. The method of claim 18 wherein the image tag ensures that the image will not be retrieved from cache.
21. The method of claim 18 wherein the image tag includes a query.
- 5 22. The method of claim 18 wherein the domain servers logged into are identified in a visited sites data structure.
23. The method of claim 22 wherein the data structure comprises a cookie.
- 10 24. A method of logging a computer system user out of multiple servers comprising:
receiving a request for a logout page;
providing a link to an expire cookies page on each server in the form of
15 an image source tag that when called causes each server to expire cookies on both the server and user's browser, and to provide an image back to the browser upon succeeding in logging out the user.
25. The method of claim 24 wherein a visited cites data structure is
20 maintained identifying the multiple servers that are logged into.
26. The method of claim 24 wherein the request is initiated by the selection of a logout link.
- 25 27. The method of claim 24 wherein the logout link may be provided on one or more of the multiple servers logged into, an affiliated server, and an authentication server.
28. The method of claim 24 wherein the cookies comprise user personal
30 information.

005190"EEH6560

29. A logout page for display on a browser used to log a user out of multiple servers, the logout page comprising:
- a plurality of image tags, each image tag corresponding to one of the multiple servers;
 - 5 each image tag providing a URL that causes a server associated with the image tag to expire cookies; and
 - each image tag forcing the browser to fetch the image from the associated server.
- 10 30. The logout page of claim 29 wherein each image tag contains a query string parameter.
31. A method of generating a logout page for display on a browser used to log a user out of multiple servers, the method comprising:
- 15 obtaining a visited sites data file which identifies each server logged into;
 - generating a plurality of image tags, each image tag corresponding to one of the multiple servers;
 - providing a URL in each image tag that causes a server associated with the image tag to expire cookies.
- 20 32. The method of claim 31 wherein each image tag contains a query string parameter causing the browser to fetch the image from the associated with the image tag with a separate transaction.
- 25